



## The NEW Advanced POTS IN A BOX® CDS-9010

The NEW Advanced POTS IN A BOX® CDS-9010 Cellular/Wi-Fi/ PSTN/ capable communications solution enables multiple combinations of legacy analog wireline in-band Voice, Machine to Machine (M2M) Data, DTMF signaling tones, analog data modem tones, FAX and Alarm system signals (all previously connected to the Public Switched Telephone Network [PSTN]), to be carried over flexible combinations of WAN/LAN/LTE Cellular Data Network.

## Features & Capabilities

- Direct plug & play Analog POTS line replacement
- (2) RJ-11 lines
- Integral Router with 1 WAN port
- 2 wired Gigabit LAN Ports
- Support for legacy FAX transmission
- Burglar and Fire Alarm signal transmission
- Ring-Down telephone line circuit
- Analog M2M native support
- Legacy Analog Modem support
- Utility Automatic Meter reading

## Supported Services

Voice Over IP via LTE | FAX | Multi-protocol support for Fire and Security Alarms | Auto Dial call boxes (Ring Down)  
Legacy Analog data support for a wide variety of FSK enabled Modems | Point of Sale terminal | M2M and SCADA  
Vending machine communications | ATM Machine Data line | Utility Automatic Meter Reading

## POTS IN A BOX®

### Cellular Backup Router

This innovative solution primarily uses the Cellular LTE Data Network, along with a firewalled Network Operating Center (NOC) to route Cellular data received to or from the PSTN to enable call origination or call completion to occur using various methods including VoIP over Cellular Data channels.

The CDS-9010 Cellular/WAN (when optioned) appliance permits connected devices to directly replace wireline analog Plain Old Telephone Service (POTS) lines and provide for multiple choices of access and connectivity.

Any application functionality that requires a traditional wireline®, dial tone-based circuit may utilize The NEW Advanced POTS IN A BOX® 9010 for connectivity. Transmission options include the ability for both Cellular Data channels and other alternative internet access pathways to provide true failover and diverse routing for calls. Additional reliability in local power outage situations is provided by an internal 24-hour capable battery. Support for location specific E-911 is also included.

- Telemetry command and control (SCADA)
- Emergency Responder Access
- SMB Router/Gateway
- Integral Wi-Fi (Host & Client)
- LTE dual Cell carrier capable
- GPS capability option
- 24-Hour power failover battery
- One number dialer capable
- Elevator, Paging, Taxi phone line (Auto dial)
- Monthly managed voice service

## Interfaces

- 2 RJ-11 for FXS ports with Voltage Protection
- 3 RJ-45 Ethernet 1 WAN/2 LAN ports  
(10/100/1000bps)
- Wi-Fi 2.4G (802.11 b/g/n, MIMO 300Mbps)
- 2 SIM Card slots (Dual Carrier)
- PCIE Card Interface (Peripheral Component Interconnect Express) USB 3.0 & 2.0
- Cellular LTE Radio Bands: 2,4,5,12,13,14,66,71
- 2 external antennas — 2.4G Dual Band Wi-Fi
- 2 antenna ports — SMA for LTE
- LED status indicators

## Power

- DC input (9VDC-16VDC) Barrel Plug
- AC Power Adapter:  
Input: 90~260V Output: 12V, 2A
- Battery: 4 or 8 cell 18650; Lithium ion
- Internal Battery Standby: Up to 24 Hours
- Battery is hot swap-able
- Graceful shutdown (Sends battery Alert)

## Environmental

- Operation Temperature: -5° C to +50° C  
(+ 23° F to + 122° F)
- Storage Temperature: -5° C to +50° C  
(+23° F to + 122° F)
- Relative Humidity: 5% to 95% Non-Cond.
- Shock: Impact tested to 75cm (30 inches) drop  
Meets GR-63-CORE standard

## Physical

- CPU 880MHz, Dual Core
- RAM: 1 Gigabit
- Injection Mold Plastic Case, Black
- Mounting bracket for wall mounting included

## Integrated Voice

- Voice over IP via LTE•VoIP
- DTMF: In-band, out of band
- PESQ > 4.3 (G.711); 3.7 (G.729)
- Echo Cancellation

## Voice Call Features

- E911 Support
- Caller ID/CWCID
- 3-way conference
- Call hold, forwarding, transfer
- Call waiting
- Ring/Hunt groups

## Optional Wired NAT Router

- DHCP Server and Client
- WWAN
- VPN
- Firewall

## Management

- Web based management Interface
- Customer management dashboard
- Line status monitoring with an alert via text
- Mass device management (TR-069)
- Flexible plans for required managed service
- Billing via Service provider or direct to customer

